

EX 221 THV

TECHNICAL SPECIFICATIONS

Excavator size	> 5 ton
Drill mast	Speedy Drill 180 Gear Box
Stroke	Standard 3100 (option 2400 max)
Pull back / down	1.500 Kg
Base frame and Kinematic	Include plate to attach to your excavator with: <ul style="list-style-type: none"> • Single slew WDL 223 for mast rotation (180°+180°) • Back feed 550 mm • Extra tilt cylinder for mast inclination • Hose reel
Hydraulics	7 proportional valves (rotation/ percussion/ feed/ slew/ slew/ back feed/ tilting)
Controls	Radio remote control and LCD screen for diagnostic and setting
Centralizer	Manual centralizer included
Data log	On request

DRILL MAST ACCESSORIES AND OPTIONS

Clamp and break device	<ul style="list-style-type: none"> • 25-90; 55-152 • Hydraulic centralizer 25,32 or 38 mm
Water pump	25 lt at 40 bars
Lubricator	1 lt / 6 lt
Dust collector	On request (depend on size)
Compressor	On request (depend on size)
Shank lubrication system	On request

SAFETY GARD OPTIONS

Manual	Manual opening type
Electronic	Electronic front guard and lateral steel guard
Hydraulic	Corner opening hydraulic type

ROTARY HEADS AND DRIFTERS

Rotary heads	RP100 /RP 200
Drifters	Doofor 430 X / 530 X / 538L