

EX 321 – S300HR

TECHNICAL SPECIFICATIONS

Excavator size	15 ton
Drill mast	S300 Gear Box
Stroke	Standard 3050 mm (option 3660 mm)
Pull back / down	2.500 Kg
Base frame and Kinematic	Include plate to attach to your excavator with: <ul style="list-style-type: none"> • Single slew WDL 419 for mast rotation (180° +180°) • Back feed 800mm • In line hose reel • Support foot for rod changer
Hydraulics	5 proportional valves (rotation/ percussion/ feed/ slew / back feed)
Controls	Radio remote control and LCD screen for diagnostic and setting
Centralizer	Manual centralizer included
Data log	On request

MAIN FRAME ACCESSORIES AND OPTIONS

90° cylinder mounted before slew for extra mast inclination
Extra slew 419 DM unit with 90° structure for extra mast inclination
Rod Changer single or carousel
180° actuator for side mast rotation

DRILL MAST ACCESSORIE AND OPTION

Clamp and break device	<ul style="list-style-type: none"> • 55-152 • Centralizer with dust collector hood • Hydraulic centralizer • Manual centralizer for 2", 3" or 4"
Water pump	25 lt at 40 bars
Lubricator	1 lt – 6 lt – 9 lt
Dust collector	On request (depend on size)
Compressor	On request (depend on size)
Shank lubrication system	On request

SAFETY GARD OPTION

Manual	Manual opening type
Electronic	Electronic front guard and lateral steel guard
Hydraulic	Corner opening hydraulic type

ROTARY HEAD AND DRIFTERS

Drifters	<ul style="list-style-type: none"> • Doofor DF550L - DF560L • Montabert HC50 - HC95
-----------------	---

SLEW + 90° CYLINDER VERSION

